



Precision Hydraulic Presses

Superior Quality Presses – Made in Italy

ADVANTAGES IN USING A LOCATELLI MECCANICA PRESS, A MACHINE WHICH IS DIFFERENT FROM OTHERS

- 1. Software to monitor the work management and production costs.** Integration with Industry 4.0 creates what has been called a “Smart Factory”;
- 2. World wide access** to the informatics systems of our presses, for analytical diagnostics and subsequent modification / update / tailoring / fine-tuning of our software;
- 3. Seven guiding points** on the ram plate for a perfect parallelism of the table: main piston + two side pistons + four guiding points, one on each column;
- 4. Part's thickness always perfect**, thanks to the exact control of pressure, timing and position. Stamping parts has never been easier;
- 5. Multiple pressing** in closed tool, for a full control of the material's flow inside the mould;
- 6. Ramps of pressure:** possibility to set the time to reach the set pressure (the operator decide, not the machine according to the metal's resistance);
- 7. Safety on the mould:** alarms on double charging, wrong charging (by standard software), missing part (by optional special device);
- 8. Memory of thousands of programs** with alphanumeric name, easy and intuitive.

* mm/s

Models	T.35 4C	T.75 4C	T.125 4C	NKT.200	T.200 4C	T.300 4C	T.400 4C	T.600 4C	T.800 4C	T.1000 4C
Height mm	2020	2120	2320	2760	2460	2605	2910	3280	3150	3230
Width mm	970	1100	1210	1470	1310	1440	1500	1670	1820	2140
Depth mm	900	1430	1360	1450	1450	1540	1670	1680	1730	2120
Front Light mm	350	360	450	560	475	575	590	695	805	980
Side Light mm	170	310	220	380	245	305	390	325	395	630
Piston's Stroke	120	150	150	150	150	150	150	200	150	200
Daylight mm	300	340	350	390	395	410	455	550	525	609
Table Size mm	350x360	360x550	450x480	500x640	475x580	575x670	590x800	695x800	805x910	980x1290
Force T	35	75	125	190	200	300	400	600	800	1000
Motor kW	3	4	7,5	7,5	15	18,5	18,5	30	30	37
Oil Kg	230	300	275	240	325	385	420	480	610	650
Down Speed *	568	480	360	242	400	390	350	383	440	350
Load Speed *	9,5	5,7	4,8	3	4	4	4	4,6	3,4	2,8
Return Speed *	490	290	350	240	350	300	300	290	295	330
Weight Kg	1300	1900	2950	4450	4000	5500	7500	11300	15000	23500